

# 4065 | 4080 | 5080D Keyline

65-80 HP





Technical data		4065
<b>ENGINE</b>		
Emission		Stage 4 / Tier 4
Manufacturer		FARMotion
Cylinders / displacement	No. / liters	3 / 2.9
Aspiration		Turbocharged
Gross power at 2,000 rpm	hp	65
Rated power at 2,200 rpm	hp	65
Max. torque @ 1,600 rpm	lb-ft	215
Torque rise	%	41
Fuel tank capacity	gal.	14.5
<b>SHUTTLE TRANSMISSION</b>		
Synchro-shuttle transmission with in-line shuttle lever		•
<b>MECHANICAL MANUAL TRANSMISSION</b>		
Speeds (Forward x Reverse)		12 x 12
Gears and Ranges		4 gears x 3 ranges
Max. transport speed	mph	18.6
Creeper gear		•
<b>REAR PTO</b>		
Mechanical activation		•
PTO speed 540 rpm		•
<b>FRONT AND REAR AXLE</b>		
Mechanical 4wd engagement		—
Mechanical differential lock engagement		—
Electro-hydraulic 4wd engagement		—
Electro-hydraulic differential lock engagement		—
<b>BRAKES AND STEERING</b>		
Mechanical parking brake		•
Hydrostatic steering with dedicated pump		•
Max. steering angle	°	55
Integrated front axle brakes		—
<b>POWER LIFT</b>		
Mechanical 3-point hitch control		•
Lifting capacity	lb	3,525
Position and draft control		•
<b>HYDRAULICS SYSTEM</b>		
Hydraulic system type		Open center
Hydraulic flow to implements	gpm	9.2
Rear remote valves		2 standard
Max. lifting capacity	lb	3,525
<b>PLATFORM</b>		
Digital dash display		•
Platform with rubber cover		•
Folding ROPS		•
Right and left side entry		•
Suspended seat		—
<b>DIMENSIONS AND WEIGHTS</b>		
With rear tires		420/70 R30
Wheelbase	in.	76.8
Max. length	in.	138.3
Max. height at roll bar	in.	97.3
Standard width	in.	72.5
Base shipping weight	lb.	5,500
Max. permissible weight	lb.	10,550

Technical data		4080
<b>ENGINE</b>		
Emission		Stage 4 / Tier 4
Manufacturer		FARMotion
Cylinders / displacement	No. / liters	3 / 2.9
Aspiration		Turbocharged
Gross power at 2,000 rpm	hp	80
Rated power at 2,200 rpm	hp	75
Max. torque @ 1,600 rpm	lb-ft	252
Torque rise	%	43
Fuel tank capacity	gal.	19.8
<b>SHUTTLE TRANSMISSION</b>		
Synchro-shuttle transmission with in-line shuttle lever		•
<b>MECHANICAL MANUAL TRANSMISSION</b>		
Speeds (Forward x Reverse)		15 x 15
Gears and Ranges		5 gears x 3 ranges
Max. transport speed	mph	25
Creeper gear		•
<b>REAR PTO</b>		
Mechanical activation		•
PTO speed 540 rpm		•
<b>FRONT AND REAR AXLE</b>		
Mechanical 4wd engagement		—
Mechanical differential lock engagement		—
Electro-hydraulic 4wd engagement		•
Electro-hydraulic differential lock engagement		•
<b>BRAKES AND STEERING</b>		
Mechanical parking brake		•
Hydrostatic steering with dedicated pump		•
Max. steering angle	°	55
Integrated front axle brakes		—
<b>POWER LIFT</b>		
Mechanical 3-point hitch control		•
Lifting capacity	lb	5,500
Position and draft control		•
<b>HYDRAULICS SYSTEM</b>		
Hydraulic system type		Open center
Hydraulic flow to implements	gpm	13.2
Rear remote valves		2 standard
Max. lifting capacity	lb	3,525
<b>PLATFORM</b>		
Digital dash display		•
Platform with rubber cover		•
Folding ROPS		•
Right and left side entry		•
Suspended seat		•
<b>DIMENSIONS AND WEIGHTS</b>		
With rear tires		420/70 R30
Wheelbase	in.	82.6
Max. length	in.	152
Max. height at roll bar	in.	97.3
Standard width	in.	72.5
Base shipping weight	lb.	6,600
Max. permissible weight	lb.	10,550

Technical data		5080D Keyline
<b>ENGINE</b>		
Emission		Stage 4 / Tier 4
Manufacturer		FARMotion
Cylinders / displacement	No. / liters	3 / 2.9
Aspiration		Turbocharged
Gross power at 2,000 rpm	hp	80
Rated power at 2,200 rpm	hp	75
Max. torque @ 1,600 rpm	lb-ft	252
Torque rise	%	43
Fuel tank capacity	gal.	19.8
<b>SHUTTLE TRANSMISSION</b>		
Synchro-shuttle transmission with in-line shuttle lever		•
<b>MECHANICAL MANUAL TRANSMISSION</b>		
Speeds (Forward x Reverse)		15 x 15
Gears and Ranges		5 gears x 3 ranges
Max. transport speed	mph	25
Creeper gear		•
<b>REAR PTO</b>		
Mechanical activation		•
PTO speed 540 rpm		•
<b>FRONT AND REAR AXLE</b>		
Mechanical 4wd engagement		—
Mechanical differential lock engagement		—
Electro-hydraulic 4wd engagement		•
Electro-hydraulic differential lock engagement		•
<b>BRAKES AND STEERING</b>		
Mechanical parking brake		•
Hydrostatic steering with dedicated pump		•
Max. steering angle	°	55
Integrated front axle brakes		•
<b>POWER LIFT</b>		
Mechanical 3-point hitch control		•
Lifting capacity	lb	5,500
Position and draft control		•
<b>HYDRAULICS SYSTEM</b>		
Hydraulic system type		Open center
Hydraulic flow to implements	gpm	13.2
Rear remote valves		3 standard
Max. lifting capacity	lb	3,525
<b>PLATFORM</b>		
Digital dash display		•
Platform with rubber cover		•
Folding ROPS		•
Right and left side entry		•
Suspended seat		•
<b>DIMENSIONS AND WEIGHTS</b>		
With rear tires		420/70 R30
Wheelbase	in.	82.6
Max. length	in.	152
Max. height at roll bar	in.	97.3
Standard width	in.	72.5
Base shipping weight	lb.	6,800
Max. permissible weight	lb.	10,550