

# 5DF ECO LINE 5DF/5DV SERIES



SPECIALIST TRACTORS  
UP TO 75 HP



TECHNICAL DATA		5D Series		
		5080.4 DV	5080.4 DF	5080.4 DF ECOLINE
ENGINE				
Manufacturer		SDF	SDF	SDF
Model		FARMotion	FARMotion	FARMotion
Emissions		Tier 4	Tier 4	Tier 4
Cylinders / displacement	No. / liters	4 / 3.8	4 / 3.8	4 / 3.8
Turbocharged & intercooled		●	●	●
Maximum power (ECE R120) @ 2000 rpm	HP / kW	75 / 55.4	75 / 55.4	75/55.4
Rated power (ECE R 120) @ 2200 rpm	HP / kW	75 / 55.4	75 / 55.4	75 / 55.4
Maximum torque	lb-ft / Nm	260 / 353 @ 1400 rpm	260 / 353 @ 1400 rpm	260 / 353 @ 1400 rpm
Torque rise	%	46	46	46
Electronic engine management		●	●	●
Standard fuel tank capacity	gal / liters	14.5 / 55	14.5 / 55	14.5 / 55
Standard fuel tank capacity with front lift + PTO	gal / liters	9.2 / 35	9.2 / 35	-
Auxiliary fuel tank	gal / liters	7.9 / 30	10.5 / 40	-
SHUTTLE				
Mechanical synchronized shuttle		-	-	●
Hydraulic power shuttle with Stop&Go system		●	●	-
MECHANICAL TRANSMISSION				
5 speed gearbox		●	●	●
Number of speeds with underdrive and creeper gear	FW+RV	-	-	30 + 15
POWERSHIFT TRANSMISSION				
5 speed gearbox		●	●	●
Number of speeds with underdrive and creeper gear	FW+RV	45 + 45	45 + 45	-
Power shift speeds	No.	3 (hi/med/lo)	3 (hi/med/lo)	-
REAR PTO				
Mechanically engaged		-	-	●
Electro-hydraulically engaged		●	●	-
PTO 540/540E		●	●	●
PTO 540/540E/1000		○	○	○
PTO 540/540E and groundspeed PTO		○	○	○
FRONT PTO				
Electro-hydraulically engaged		●	●	-
PTO 1000 rpm		○	○	-
AXLES AND BRAKES				
Four wheel drive engagement		Electro-hydraulic	Electro-hydraulic	Mechanical
Differential lock engagement		Electro-hydraulic	Electro-hydraulic	Mechanical
Independent parking brake		●	●	●
Hydraulic trailer braking system		●	●	●
Hydrostatic steering with independent pump		●	●	●
Axle steering angle	degrees	60	60	60
HITCH				
Mechanical rear hitch		●	●	●
Electronic rear hitch		○	○	-
Rear lift capacity	lb / kg	5,730 / 2600	6,170 / 2800	6,170 / 2800
Front hitch		○	○	-
Front hitch capacity	lb / kg	3,300 / 1500	3,300 / 1500	-
HYDRAULIC SYSTEM				
Fixed displacement pump (standard)	gpm / lpm	14.3 / 54	14.3 / 54	11.9 / 45
Fixed displacement double pump (optional)	gpm / lpm	16.9 / 64	16.9 / 64	-
Rear hydraulic remote valves	No.	Up to 3	Up to 3	Up to 3
Mid mounted hydraulic remote couplers	No.	Up to 3	Up to 3	-
OPEN STATION				
Straddle-type platform		-	-	●
Digital front display		-	-	●
2-post safety frame		-	-	●
Vinyl seat with mechanical suspension		-	-	●
Horizontal exhaust		-	-	●

Technical data is based on manufacturer's estimates. In order to deliver a product that is more and more in line with your needs, DEUTZ-FAHR reserves the right to update the specifications of its machines at any time without notice.



TECHNICAL DATA		5D Series		
		5080.4 DV	5080.4 DF	5080.4 DF ECOLINE
CAB				
4-post structure suspended on silent-block mounts		●	●	-
HVAC system		●	●	-
Horizontal exhaust		●	●	-
DIMENSIONS AND WEIGHTS				
Front axle width (flange to flange)	in / mm	39.8 / 1011	51 / 1296	51 / 1296
Rear axle width (flange to flange)	in / mm	33.6 / 854	48.1 / 1221	48.1 / 1221
Overall rear fender width (min-max)	in / mm	45.8-50.9 / 1163-1293	57.2-64.4 / 1454-1642	57.1-76.5 / 1450-1944
Front tires		240/70R16	280/70R16	280/70R16
Rear tires		380/70R20	380/70R24	380/70R24
Length from front clevis support to the rear lift arm in lower position	in / mm	155.9 / 3959	155.2 / 3942	155.2 / 3942
Minimum overall width	in / mm	50.9 / 1293	62.5 / 1588	57.1 / 1450
Height at cab	in / mm	89.4 / 2271	91.4 / 2321	-
Height at safety frame	in / mm	-	-	96.2 / 2444
Height at engine hood	in / mm	58 / 1473	54.8 / 1393	54.8 / 1393
Height at rear fenders	in / mm	49.8 / 1265	46.1 / 1170	46.1 / 1170
Ground clearance (front axle)	in / mm	9.2 / 233	9.7 / 247	9.7 / 247
Wheelbase	in / mm	85.8 / 2180	84.3 / 2141	84.3 / 2141
Approx. base weight (min-max)	lb / kg	6,237-6,768 / 2829-3070	6,056-6,889 / 2747-3125	6,106 / 2770
Maximum permissible total weight	lb / kg	10,141 / 4600	11,023 / 5000	11,023 / 5000

●: standard    ○: optional    -: not available    Dimensions are approximates, and can vary slightly.





Dealer



Deutz-Fahr logo is a registered trademarks of SAME DEUTZ-FAHR in the U.S. and/ or other countries. PFG America is a registered trademark of Power Farming, Ltd, and is the approved distributor of the Deutz-Fahr brand in the USA. 2017 PFG America. All Rights Reserved. The standard and optional equipment and the availability of individual models might vary from one country to the next. PFG America reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to make such modifications to units already sold. While every effort is made to ensure that the specifications, descriptions, and illustrations in this brochure are correct at the time of printing, these are also subject to change without prior notice. Illustrations might show optional equipment, and might not show all standard equipment.