

9 SERIES



DEUTZ-FAHR  
9340 TTV Agrotron







GENERATE MORE POWER, SAVE FUEL, REDUCE EMISSIONS, INCREASE OPERATING EFFICIENCY, WORK COMFORTABLY, CONSUME FEWER RESOURCES, IMPROVE ACCURACY. DRIVE A 9 SERIES, AND EXCEL IN YOUR FIELD.

CCLS HYDRAULIC SYSTEM WITH  
UP TO 55 GPM FLOW

MULTI-FUNCTION ARMREST  
CONTROL CENTER

POWERFUL AND EFFICIENT DEUTZ®  
7.8 LITER, 6-CYLINDER ENGINE

SINGLE PIECE RAISING HOOD  
ELECTRO-HYDRAULICALLY  
OPERATED

FRONT 3-POINT HITCH  
WITH 11,000 LB LIFT  
CAPACITY

AVAILABLE  
FRONT PTO

SUSPENDED FRONT AXLE

AGROSKY AUTO GUIDANCE / STEERING READY



MAXIVISION2 CAB WITH  
PNEUMATIC SUSPENSION

12" COLOR, TOUCH-SCREEN  
UNIVERSAL MONITOR IN ARMREST

ISOBUS (ISO 11783)  
CONNECTIVITY

TTV (CVT) TRANSMISSION  
FROM ZF®

MASSIVE 26,450 LB  
REAR LIFT CAPACITY

540E/1000/1000E  
REAR PTO

UP TO 6 REAR  
REMOTE VALVES

FOLDING  
INSTRUCTOR'S SEAT

32 MPH (50 KPH) TRANSPORT SPEED



<b>Technical data</b>		<b>9340 TTV AGROTRON</b>	
<b>ENGINE</b>			
Manufacturer			Deutz
Model			TTC D 7.8 L06
Emissions			Tier 4 final
Cylinders / Displacement	No. / liters		6 / 7.8
In-line twin turbochargers and intercooled			•
Electronic-viscstatic fan			•
Deutz Common Rail (DCR) direct fuel injection	PSI / bar		29,000 / 2000
Rated power (ECE R120) @ 2100 rpm	HP / kW		316 / 232
Max. Power (ECE R 120) @ 1900 rpm	HP / kW		336 / 247
Max. torque	lb-ft / Nm		1,010 / 1372
Torque rise	%		30
Engine speed at maximum torque	rpm		1500
Electronic engine management			•
Air filter with dust ejector			•
Exhaust after treatment (EGR+DPF+SCR)			•
Fuel tank capacity	gal / liters		158 / 600
AdBlue® (DEF) tank capacity	gal / liters		14.5 / 55
<b>TTV TRANSMISSION</b>			
Manufacturer			ZF
Model			Terramatic TMT 32
Number of ranges	No.		4
Maximum transport speed	mph / kph		32 / 50
PowerZero			•
Cruise control speeds	No.		2 forward + 2 reverse
Driving strategies (Auto / Manual / PTO)			•
Eco/Power control			•
Hydraulic reverse power shuttle			•
Shuttle modulation control (5 adjustment levels)			•
<b>PTO</b>			
Rear PTO 540E/1000/1000E			•
AUTO PTO			•
Front PTO with 6-spline shaft, 1000 rpm speed			○
<b>AXLES AND BRAKES</b>			
Suspended front axle			•
Front wheel drive electro-hydraulically engaged			•
Electro-hydraulically operated front and rear differential lock			•
EPB (Electronic Parking brake)			•
Four-wheel braking system with automatic 4WD			•
External dry disc brakes on the front axle			○
Hydraulic power braking			•
Hydraulic trailer braking system			○
Pneumatic trailer braking system			○
<b>HYDRAULIC SYSTEM AND HITCH</b>			
Pump output (std)	gpm / lpm		42 / 160
Pump output (opt)	gpm / lpm		55 / 210
Closed center hydraulic system (load sensing)			•
Max. usable oil volume	gal / liters		26 / 100
Separate transmission / hydraulic reservoirs			•
Rear electro-hydraulic remote valves	No.		6 max.
Front remote valves	No.		2 max.
Rear 3-point hitch with electronic operation			•
Rear hitch lift capacity	lb / kg		26,450 / 12000
Front 3-point hitch			•
Front hitch lift capacity	lb / kg		11,000 / 5000
<b>ELECTRICAL SYSTEM</b>			
Voltage	V		12
Standard battery	Ah / Amp		180 / 700
Alternator	Amp		2 x 200

Technical data is based on manufacturer's estimates. In order to deliver a product that is more and more in line with your needs, DEUTZ-FAHR reserves the right to update the specifications of its machines at any time without notice.

## Technical data

## 9340 TTV AGROTRON

Starter motor	hp / kW	5.4 / 4.0
External power socket		•
ISO 11786 implement plug in cab (7-pin)		○
<b>CAB</b>		
MaxiVision Cab 2		•
Pneumatic cab suspension		•
Adjustable telescopic rear view mirrors		•
Heated adjustable rear view mirrors with LED lights		○
Air conditioning		•
Automatic climate control system		○
Openable roof hatch		•
MaxCom multifunction armrest		•
Multifunction joystick		•
WorkMonitor		•
Light control panel		•
iMonitor2 color, touch-screen, 12" universal terminal		•
Remote camera system		○
Agrosky automatic steering and guidance system		○
ISO 11783 (ISOBUS Class 3) with external plug		○
Comfortip Professional headland management system		•
Max Comfort Dynamic Seat XL ++ (dynamic low frequency suspension)		•
Max Comfort Dynamic Seat XXL ++ (dynamic suspension, low frequency horizontal suspension)		○
Cushioned instructor's seat		•
"Radio Ready" for audio system with antenna and speakers		•
Halogen work lights		•
Full-LED work lights		○
<b>DIMENSIONS AND WEIGHTS</b>		
With front tires		650/65R34
With rear tires		710/75R42
Wheelbase	in / mm	123 / 3135
Length	in / mm	207 / 5268
Height	in / mm	138 / 3500
Width	in / mm	100-108 / 2550 - 2750
Ground clearance	in / mm	16-17 / 410 - 440
Total unladen weight	lb / kg	26,450 / 12000
Max. permissible total weight	lb / kg	39,683 / 18000

•: standard ○: optional



Dealer



Deutz-Fahr logo is a registered trademarks of SAME DEUTZ-FAHR in the U.S. and/ or other countries. PFG America is a registered trademark of Power Farming, Ltd, and is the approved distributor of the Deutz-Fahr brand in the USA. 2017 PFG America. All Rights Reserved. The standard and optional equipment and the availability of individual models might vary from one country to the next. PFG America reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to make such modifications to units already sold. While every effort is made to ensure that the specifications, descriptions, and illustrations in this brochure are correct at the time of printing, these are also subject to change without prior notice. Illustrations might show optional equipment, and might not show all standard equipment.