

		5KF SERIES		
Technical data		5080 KF - Rubber Track	5080 KF - Steel Track Narrow	5080 KF - Steel Track Wide
ENGINE		NODDO! !!GON		
Emission			Stage 4 / Tier 4	
Manufacturer		FARMotion		
Cylinders / displacement	No. / liters	3/2.9		
Bore x stroke	in	4.1 × 4.5		
Aspiration		Turbocharged with intercooling		
High-pressure injection		Common rail @ 29,000 PSI (2,000 bar)		
Gross power at 2,000 rpm	НР	80		
Rated power at 2,200 rpm	HP	75		
Max. torque @ 1,600 rpm	lb-ft / Nm	252 / 342		
Torque rise	%	43%		
Fuel tank capacity	gal	25		
SHUTTLE TYPE	Sur			
Synchro-shuttle transmission		•		
Single disc cutch diameter	in	12		
MECHANICAL MANUAL TRANSMISSION			12	
Speeds (Forward x Reverse)			16 x 16	
Gears and ranges		4 gears x 4 ranges		
Min Max. speed	mph	4 gears x 4 ranges 0.93 - 8.8		
REAR PTO	Пірп		0.55 - 6.6	
PTO type			Independent, 540/540E	
PTO clutch		Wet disc clutch		
PTO activation		Push button		
STEERING SYSTEM			Fusii buttoii	
Steering system type			Hydraulic-assisted clutch and brake st	ooring
Steering system type Steering control		2 hand levers		
POWER LIFT			2 Harid tevers	
Mechanical 3-point hitch control			•	
Lifting capacity	lb	6,850		
Position and draft control	· · ·	0,650		
HYDRAULICS SYSTEM				
Hydraulic system type			Open center	
Total hydraulic flow	gom	19.8		
Flow to remote valves and hitch	gpm	13.2		
Rear remote valves	gpm	3 std		
Mid couplers		2 sets of couplers		
PLATFORM			2 sets of couplers	
			•	
Digital dash display Folding ROPS Canopy			•	•
Suspended vinyl seat		•	•	
DIMENSIONS AND WEIGHTS				
Axle spacing	in	65.5	65.0	65.0
Track length	in	44.9	41.3	53.15
Track tength Track width	in	44.9 15.7	12.2	15.7
Irlack width Idlers / rollers				5 bottom / 1 top
Track contact area	ft ²	5 bottom / 1 top 11.0	5 bottom / 1 top 14.2	14.2
				134.6
Tractor length	in	134.6	134.6	68
Tractor Width	in	60.2	53.5	7.9
Groung clearance	in	7.9	7.9	
Height over safety frame	in	103.5	103.5	103.5
Base shipping weigh	lb	9,500	9,390	11,574

Technical data is based on manufacturer's estimates. In order to deliver a product that is more and more in line with your needs, DEUTZ-FAHR reserves the right to update the specifications of its machines at any time without notice.

•: standard O: optional -: not available