

9 SERIES AGROTRON



DEUTZ-FAHR
9340 TTV Agrotron



SOME OPTIONS AND/OR SPECIFICATIONS SHOWN MAY NOT BE AVAILABLE IN ALL MARKETS

9 SERIES TTV Agrottron

9340

Technical data

Description	Item	
ENGINE		
Manufacturer		Deutz
Model		TTCD 7.8 L06
Emissions		Tier4 final
Cylinders/Capacity	No./liters	6 / 7.775
Double-Turbo		•
Electronic-viscstatic fan		•
Deutz Common Rail (DCR)	PSI/bar	29,000 / 2000
Max. power (ECE R120)	hp/kW	336/247
Power at rated engine speed (ECE R 120)	hp/kW	316/232
Engine speed at maximum power	rpm	1900
Rated engine speed	rpm	2100
Max. torque	lb-ft/Nm	1,011/1372
Engine speed at maximum torque	rpm	1500
Electronic engine governor		•
Air filter with dust ejector		•
Fuel tank capacity	gal/liters	158/600
DEF (AdBlue®) tank capacity	gal/liters	14.555
TTV TRANSMISSION		
Model		ZF Terramatic TMT 32
Max. speed	mph/kph	25-31-37/40-50-60
Overspeed (60 kph Eco)		•(1780 rpm)
Overspeed (50 kph Eco)		•(1480 rpm)
Overspeed (40 kph SuperEco)		•(1300 rpm)
PowerZero		•
CruiseSpeed	No.	2 forward + 2 reverse
Driving Strategies (Auto/Manual/PTO)		•
Eco/Power control		•
Reverse power shuttle		•
SenseClutch		•
PTO		
PTO 540E/1000/1000E		•
Front PTO 1000		○
Front PTO 1000E		○
AXLES AND BRAKES		
Suspended front axle		•
Electronically engaged 4-wheel drive		•
100 % front/rear differential lock		•
ASM system		•
Braking system with automatic 4-wheel drive engagement		•
External disc brakes		○
Powerbrake		•
Electric Parking Brake (EPB)		•
HYDRAULIC SYSTEM AND HITCH		
Pump output (std)	gpm/lpm	42/160
Pump output (opt)	gpm/lpm	55/210
Closed centre hydraulic system (Load Sensing)		•
Max. usable oil volume	gal/liters	26/100
Separate additional oil tank		•
Auxiliary hydraulic distributors (std)	No. of valves	4
Auxiliary hydraulic distributors (opt)	No. of valves	5/6/7/8
Rear hitch electronic		•
Rear lift capacity	lb/kg	26,450/12000
Front hitch		•
Front lifting capacity	lb/kg	11,000/5000
ELECTRICAL SYSTEM		
Voltage	V	12
Standard battery	V/Ah/A	12/180/700
Alternator	V/A	12/2x200

Technical data		9 SERIES TTV Agrottron	
		9340	
Starter motor	V/kW	12/4.0	
External power socket		●	
CAB			
MaxiVision Cab 2		●	
Pneumatic suspension		●	
Adjustable rear view mirrors		●	
Heated adjustable rear view mirrors		○	
Air conditioning		●	
Automatic A/C system		○	
High visibility roof		●	
MaxCom multifunction armrest		●	
Multifunction joystick		●	
WorkMonitor		●	
Light control panel		●	
iMonitor 2.0		○	
Agrosky ready		○	
ISOBUS compatibility		○	
Comfortip Professional		○	
Max Comfort Dynamic Seat XL ++ (dynamic low frequency suspension)		●	
Max Comfort Dynamic Seat XXL ++ (dynamic suspension, low frequency horizontal suspension)		○	
Upholstered instructor's seat		●	
Wiring for audio system with speakers		●	
Halogen work lights		●	
Full-LED work lights		○	
Xenon work lights		○	
HITCHES			
Automatic towing hitch		●	
Height adjustable ball hitch		○	
Fixed ball automatic hitch		○	
Upper link		○	
Hydraulic upper link		○	
Pickup hitch		○	
Piton Fix		○	
DIMENSIONS AND WEIGHTS			
With front tires		650/65R34	
With rear tires		710/75R42	
Wheelbase	in/mm	123/3135	
Length	in/mm	207/5268	
Height	in/mm	138/3500	
Width	in/mm	100-108/2550 - 2750	
Ground clearance	in/mm	16-17/410 - 440	
Front unladen weight	lb/kg	10,675/4850	
Rear unladen weight	lb/kg	15,750/7150	
Total unladen weight	lb/kg	26,450/12000	
Max. permissible front weight	lb/kg	16,525/7500	
Max. permissible rear weight	lb/kg	26,450/12000	
Max. permissible total weight	lb/kg	39,675/18000	

Technical data and pictures are manufacturer's estimates. DEUTZ-FAHR reserves the right to update the specifications of its machines at any time without notice.

●: standard ○: optional -: not available

Dealer

Distributor:
PFG America, LLC
535 Hurricane Shoals Court
Suite 100
Dacula, GA 30019
www.deutz-fahramerica.com



Deutz-Fahr and its logos are trademarks of Same Deutz-Fahr Italia S.P.A. in the U.S. and other countries used under license by PFG America, LLC. PFG America and logo are trademarks licensed to PFG America, LLC, which is the exclusive distributor of the Deutz-Fahr brand in the USA. Other logos are the trademarks of their respective owners. The standard and optional equipment and the availability of individual models might vary from one country to the next. PFG America reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without any obligation whatsoever to make such modifications to units already sold. This brochure is for descriptive purposes only and while reasonable efforts were made to ensure that the specifications, descriptions, and illustrations in this brochure are correct at the time of printing, these are also subject to change without prior notice. Illustrations might show optional equipment, and might not show all standard equipment. PFG America disclaims all representations and warranties, express or implied, or any liability from the use or reliance upon this brochure. Power and other specifications are based on various standards or recommended practices not addressed herein. ©2018 PFG America, LLC. All Rights Reserved.