

			5KF SERIES	
Technical data		5080 KF - Rubber Track	5080 KF - Steel Track Narrow	5080 KF - Steel Track Wide
ENGINE				
Emission			Stage 4 / Tier 4	
Manufacturer			FARMotion	
Cylinders / displacement	No. / liters	3 / 2.9		
Bore x stroke	in	4.1 x 4.5		
Aspiration		Turbocharged with intercooling		
High-pressure injection		Common rail @ 29,000 PSI (2,000 bar)		
Gross power at 2,000 rpm	HP	80		
Rated power at 2,200 rpm	HP	75		
Max. torque @ 1,600 rpm	lb-ft / Nm	252 / 342		
Torque rise	%	43%		
Fuel tank capacity	gal	25		
SHUTTLE TYPE				
Synchro-shuttle transmission		•		
Single disc cutch diameter	in	12		
MECHANICAL MANUAL TRANSMISSION				
Speeds (Forward x Reverse)			16 x 16	
Gears and ranges		4 gears x 4 ranges		
Min Max. speed	mph	0.93 - 8.8		
REAR PTO			0.55 0.0	
PTO type			Independent, 540/540E	
PTO clutch		Wet disc clutch		
PTO activation		Push button		
STEERING SYSTEM				
Steering system type			Hydraulic-assisted clutch and brake st	eering
Steering control		2 hand levers		
POWER LIFT				
Mechanical 3-point hitch control			•	
Lifting capacity	lb	6,850		
Position and draft control			•	
HYDRAULICS SYSTEM			-	
Hydraulic system type			Open center	
Total hydraulic flow	gpm	19.8		
Flow to remote valves and hitch	gpm	13.2		
Rear remote valves	or	3 std		
Mid couplers		2 sets of couplers		
PLATFORM				
Digital dash display		•	•	
Folding ROPS Canopy		•	•	•
Suspended vinyl seat		•	•	
DIMENSIONS AND WEIGHTS				
Axle spacing	in	65.5	65.0	65.0
Track length	in	44.9	41.3	53.15
Track width	in	15.7	12.2	15.7
Idlers / rollers		5 bottom / 1 top	5 bottom / 1 top	5 bottom / 1 top
Track contact area	ft²	11.0	14.2	14.2
Tractor length	in	134.6	134.6	134.6
Tractor Width	in	60.2	53.5	68
Groung clearance	in	7.9	7.9	7.9
oroung elearance		103.5	103.5	103.5
Height over safety frame	in			

Technical data is based on manufacturer's estimates. In order to deliver a product that is more and more in line with your needs, DEUTZ-FAHR reserves the right to update the specifications of its machines at any time without notice.

•: standard O: optional -: not available